

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 816 731 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
15.01.2003 Bulletin 2003/03

(51) Int Cl.7: **F16K 27/00, F15B 13/00**

(21) Application number: **97110210.8**

(22) Date of filing: **23.06.1997**

(54) **Manifold valve**

Ventilverteiler

Soupape distributrice

(84) Designated Contracting States:
CH DE FR GB IT LI NL

(30) Priority: **25.06.1996 JP 16467396**

(43) Date of publication of application:
07.01.1998 Bulletin 1998/02

(73) Proprietors:

- Ohmi, Tadahiro
Sendai-shi, Miyagi (JP)
- FUJIKIN INCORPORATED
Osaka-shi, Osaka (JP)

(72) Inventors:

- Ohmi, Tadahiro
Sendai-shi, Miyagi (JP)
- Yamaji, Michio, c/o FUJIKIN INCORPORATED
Osaka-shi, Osaka (JP)

- Ikeda, Nobukazu, c/o FUJIKIN INCORPORATED
Osaka-shi, Osaka (JP)
- Hatano, Masajuki, c/o FUJIKIN INCORPORATED
Osaka-shi, Osaka (JP)
- Yokoyama, Kusuke,
c/o FUJIKIN INCORPORATED
Osaka-shi, Osaka (JP)
- Tanaka, Shigeaki, c/o FUJIKIN INCORPORATED
Osaka-shi, Osaka (JP)

(74) Representative: **Paul, Dieter-Alfred, Dipl.-Ing. et al**
Paul & Albrecht,
Patentanwaltssozietät,
Hellersbergstrasse 18
41460 Neuss (DE)

(56) References cited:

EP-A- 0 619 450 **EP-A- 0 754 896**
US-A- 3 384 114

BEST AVAILABLE COPY

EP 0 816 731 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

BACKGROUND OF THE INVENTION

[0001] The present invention relates to shutoff-opening devices comprising a valve main body and a plurality of valve actuators and fluid control apparatus comprising such devices.

[0002] The terms front, rear, upper, lower, right and left are herein used based on FIG. 2; the right-hand side, the left-hand side, the upper side and lower side of the drawing are referred to as front, rear, upper and lower, respectively, and the terms right and left are used for the device as it is viewed from the behind toward the front. The device may be used with the front-rear relationship as reversed, or the upper and lower side thereof positioned as the left and right sides.

[0003] Shutoff-opening devices are already known which comprise a rectangular parallelepipedal valve main body, and a plurality of valve actuators. Such a device is disposed at each of the inlet side and the outlet side of a massflow controller or like controller to provide a fluid control apparatus for use in semiconductor manufacturing equipment.

[0004] FIG. 17 shows a conventional shutoff-opening device 61 according to the preamble of claim 1.

[0005] When a fluid flows from the main channel 67 into the first subchannel 68, the dead volume (stagnant portion of fluid) of the device 61 is only short channels 71, 72 connecting the main channel 67 to the second and third actuators 65, 66. When the fluid flows from the main channel 67 into the second channel 69, the dead volume is the short channel 72 interconnecting the main channel 67 and the third valve actuator 66, and front end portions 67a, 67b of the main channel 67 positioned between the first valve actuator 64 and the second valve actuator 65. Further when the fluid flows from the main channel 67 into the third subchannel 70, the dead volume is the short channel 71 interconnecting the main channel 67 and the second valve actuator 65, the main channel front end portions 67a, 67b positioned between the first and second valve actuators 64, 65, and an intermediate portion 67c of the main channel 67 positioned between the second and third actuators 65, 66.

[0006] With the shutoff-opening devices and fluid control devices for use in semiconductor manufacturing equipment, it is critical to diminish the dead volume which reduces the purity of the process gas. It is also required that these devices be reduced in content volume, entire volume and weight, whereas the conventional devices still remain to be improved in these points.

SUMMARY OF THE INVENTION

[0007] An object of the present invention is to provide shutoff-opening devices which are diminished in dead volume, volume and weight as compared with conventional devices and to provide fluid control devices com-

prising such shutoff-opening devices.

[0008] The present invention provides a shutoff-opening device according to claim 1.

[0009] The forwardly downward inclination of the slanting face is preferably 15 degrees to 60 degrees, more preferably 20 degrees to 45 degrees. If the inclination is small, the advantage resulting from this feature is small, whereas if the inclination is great, the front-end valve actuator becomes forwardly projected beyond the front end of the valve main body, increasing the possibility of the actuator interfering with other members. Thus, the inclination should be within the preferred range described in view of the size of the valve actuators and the size of the fluid control apparatus to be provided by such shutoff-opening devices.

[0010] With the shutoff-opening device of the present invention, the upper surface of the valve main body is in the form of a slanting face extending forwardly downward at the portion thereof having the front-end valve actuator mounted thereon. This reduces the volume of the front upper portion of the valve main body, the front-to-rear length of the front portion thereof, and the content volume, volume and weight of the shutoff-opening device. The main channel includes a front end portion positioned between the front-end valve actuator and the valve actuator immediately adjacent thereto which portion accounts for a major portion of the dead volume of the shutoff-opening device. This main channel front end portion diminishes with the reduction in the length of front portion of the valve main body, consequently decreasing the dead volume of the shutoff-opening device.

[0011] The shutoff-opening device is provided, for example, at each of the inlet side and the outlet side of a massflow controller or like controller to constitute a fluid control device for use in semiconductor manufacturing equipment.

[0012] Among the subchannels of each shutoff-opening device in this case, it is desired to use the subchannel remotest from the controller for the process gas and to use the subchannel adjacent to this subchannel for a purge gas. The dead volume during the flow of the process gas is then limited to a short channel or short channels connecting the main channel to the other valve actuator or actuators toward the rear, with the result that the gas remaining upon changing over the process gas to other gas can be removed within a short period of time.

[0013] A suitable number of fluid control devices of the type described are used for providing a fluid control apparatus. It is desired in this case that the valve main bodies of the shutoff-opening devices be equal in front-to-rear length irrespective of the number of valve actuators. The first valve actuators of the shutoff-opening devices are then aligned, rendering the shutoff-opening devices easy to operate.

[0014] Preferably, the subchannel included in the subchannels of each shutoff-opening device and communicating with the main channel via the front-end valve

actuator has an opening formed in a front end face or lower surface of the valve main body, the other subchannel or subchannels have an opening in the lower surface of the valve main body, and piping for the other subchannel or subchannels is provided under the main body. The piping means can then be in a flat arrangement under the valve main body, compacting the control apparatus in its entirety and assuring the piping portion of facilitated maintenance.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015]

FIG. 1 is a perspective view showing a first embodiment of shutoff-opening device of the invention;
 FIG. 2 is a view in longitudinal section of the same;
 FIG. 3 is a perspective view showing a first embodiment of a fluid control device of the invention;
 FIG. 4 is a view in longitudinal section of the same;
 FIG. 5 is a perspective view showing a second embodiment of shutoff-opening device of the invention;
 FIG. 6 is a perspective view showing a second embodiment of fluid control device of the invention;
 FIG. 7 is a view in longitudinal section showing a third embodiment of shutoff-opening device of the invention;
 FIG. 8 is a view in longitudinal section showing a fourth embodiment of shutoff-opening device of the invention;
 FIG. 9 is a plan view showing an embodiment comprising a plurality of shutoff-opening devices of the invention;
 FIG. 10 is a plan view showing another embodiment comprising a plurality of shutoff-opening devices of the invention;
 FIG. 11 is a perspective view showing a fifth embodiment of shutoff-opening device of the invention;
 FIG. 12 is a view in longitudinal section of the same;
 FIG. 13 is a perspective view showing a fluid control device embodying the invention and comprising shutoff-opening devices according to the fifth embodiment;
 FIG. 14 is a view in longitudinal section of the same;
 FIG. 15 is a perspective view showing a sixth embodiment of shutoff-opening device of the invention;
 FIG. 16 is a view in longitudinal section of the same; and
 FIG. 17 is a view in longitudinal section showing a conventional shutoff-opening device.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0016] Embodiments of the invention will be described below with reference to the drawings.

[0017] FIGS. 1 and 2 show a first embodiment of shutoff-opening device 1 of the invention. As shown in FIGS.

3 and 4, the shutoff-opening device 1 is disposed at the inlet side and the outlet side of a massflow controller 2 to provide a fluid control device 10.

[0018] With reference to FIGS. 1 and 2, the shutoff-opening device 1 comprises a generally rectangular parallelepipedal valve main body 3, and first (front-end), second (intermediate) and third (rear-end) channel opening-closing valve actuators 4, 5, 6. The valve main body 3 is internally formed with a main channel 21 extending straight from the rear end face of the main body 3 nearly to the location of the front-end valve actuator 4 longitudinally of the body, and first (front-end), second (intermediate) and third (rear-end) subchannels 22, 23, 24 communicating with the main channel 21 via the valve actuators 4, 5, 6, respectively. The subchannels 23, 24 communicating with the main channel 21 via the respective second and third valve actuators 5, 6 are positioned immediately in the rear of respective short channels 25, 26 extending from the main channel 21 to the second and third valve actuators 5, 6, whereas these subchannel 23, 24 are shown in broken lines as shifted leftward from the actual locations (the same as hereinafter).

[0019] The valve main body 3 is integral with a block-like extension 7 extending from a right wall 3c of the portion thereof having the actuators 4, 5, 6 attached thereto. The extension 7 is formed with the second and third subchannels 23, 24 and serves as a screw fastening portion.

[0020] The upper surface of the valve main body 3 includes a mount face 3a in the form of a slanting face extending forwardly downward for mounting the front-end actuator 4 thereon. The remaining portion of the upper surface, i.e., a mount face 3b for the second and third actuators 5, 6, is flat and parallel to the lower surface of the body 1.

[0021] The valve actuators 4, 5, 6 are attached to the mount faces 3a, 3b perpendicular thereto. The valve main body 3 has a cavity 18 for inserting the first actuator 4, and cavities 19 for inserting the respective second and third actuators 5, 6. The cavity 18 has a smaller depth than the cavities 19. Accordingly, the first actuator 4 is shorter than the other actuators 5, 6. The valve actuators can be of the same length for insertion into cavities of the same depth. The first and third actuators 4, 6 are of the normally closed type, and the second actuator 5 of the normally open type.

[0022] The main channel 21 extends from the rear end face of the main body 3 to a location close to the front end face thereof. The first subchannel 22 has an opening in the front end face of the body 3. The front end face of the main body 3 is provided with a fitting 9 having a nut for connecting a check valve, pressure regulator or the like to the first subchannel 22. The second and third subchannels 23, 24 extend through the extension 7 of the main body 3 and each have an opening in the lower surface of the body 3.

[0023] With reference to FIG. 2, the dead volume of

the device 1 is only the short channels 25, 26 connecting the main channel 21 to the respective second and third valve actuators 5, 6 when a fluid flows from the main channel 21 into the first subchannel 22. When the fluid flows from the main channel 21 into the second subchannel 23, the dead volume is the short channel 26 connecting the main channel 21 to the third actuator 6, and front end portions 21a, 21b of the main channel 21 which are positioned between the first and second actuators 4, 5, forming an obtuse angle. When the fluid flows from the main channel 21 into the third subchannel 24, the dead volume is the short channel 25 connecting the main channel 21 to the second actuator 5, the main channel front end portions 21a, 21b positioned between the first and second actuators 4, 5, and an intermediate portion 21c of the main channel 21 positioned between the second and third actuators 5, 6.

[0024] With the shutoff-opening device 1 described, the first actuator mount face 3a included in the upper surface of the valve main body 3 is made equal in area to the first actuator mount face 63a of the conventional shutoff-opening device 61 shown in FIG. 17. Accordingly, the volume of the front upper portion of the valve main body 3 and the front-to-rear length of the front portion of the body are made smaller than in the conventional shutoff-opening device 61 by an amount attributable to the formation of the forwardly downward slanting face serving as the mount face 3a, consequently diminishing the content volume, overall volume and weight of the shutoff-opening device 1. Suppose the length of the first valve actuator mount face 63a of the conventional shutoff-opening device 61 is L , and the inclination of the slanting face is θ . The shutoff-opening device 1 is reduced by $L(1 - \cos \theta)$ in front-to-rear length, and by $L^2 \times \cos \theta \times \sin \theta \div 2$ in vertical section. With respect to the dead volume, the combined volume of the obtuse angle forming front end portions 21a, 21b of the main channel 21 is made smaller than the combined volume of the front end portions 67a, 67b of the main channel 67 of the conventional shutoff-opening device 61 owing to the reduction in the length of the valve main body 3, whereby the dead volume of the entire shutoff-opening device 1 is also diminished. As the inclination increases, the front end portion 21a extending straight from the portion 21c of the main channel 21 diminishes with an increase in the length of the bent front end portion 21b. However, the diminution of the overall dead volume increases with an increase in the inclination.

[0025] FIGS. 3 and 4 show a fluid control device, which comprises a massflow controller 2, and the shutoff-opening device 1 installed at each of the inlet side (left side in FIG. 4) and the outlet side (right side in FIG. 4). The shutoff-opening device 1 shown in FIGS. 1 and 2 is mounted on the inlet side with their front and rear ends reversed.

[0026] With the shutoff-opening device 1 at the inlet side, the first subchannel 22 remotest from the massflow controller 2 is used for the inflow of process gas, the

second subchannel 23 adjacent to the subchannel 22 for the inflow of purge gas, and the third subchannel 24 closest to the controller 2 for evacuation. With the shutoff-opening device 1 at the outlet side, the first subchannel 22 remotest from the controller 2 is to communicate with a process chamber, and the second subchannel 23 with an exhaust gas duct to serve as a purge port.

[0027] An upper channel block 11 having a channel 11a opened at its lower surface is provided in a projecting manner at the lower end of each of the inlet and outlet sides of the massflow controller 2. A lower channel block 12 is disposed beneath the block 11. The lower and upper channel blocks 12, 11 are fastened together by two controller installing screws 13 screwed into the upper block 11 from above. The lower block 12 is formed with a channel 12a for holding the channel 11a of the upper block 11 in communication with the main channel 21 of the valve main body 3. The lower block 12 is fastened to the valve main body 3 with device installing screws 14 driven in through the lower block 12. Piping channel blocks 15, 16 for the respective second and third subchannels 23, 24 are fastened to the extension 7 with piping installing screws 17 driven in through the extension 7 from above. The third subchannel 24 of the inlet-side shutoff-opening device 1 and the third subchannel 24 of the outlet-side shutoff-opening device 1 are connected to a vacuum pump (not shown) after their piping channel blocks 15, 16 are interconnected by a pipe 27. A fitting 28 is attached to the lower side of the block 16 for the second subchannel 23. The fitting 28 has a pipe joint portion which is positioned at a lower level than the evacuation pipe 27. The purge gas piping is therefore unlikely to interfere with the evacuation pipe 27. When the fluid control device 10 is to be installed, the massflow controller 2 and the shutoff-opening devices 1 are mounted on the upper surface of a base plate 29 with the piping channel blocks 15, 16 positioned beneath the lower surface of the base plate 29 as shown in FIG. 4.

[0028] If the massflow controller 2 of the fluid control device 10 malfunctions, the controller 2 is removable upward for replacement by removing the controller installing screws 13. Further if the shutoff-opening device 1 fails, the device 1 can be removed upward for replacement by removing the device installing screws 14 and the piping installing screws 17.

[0029] When the process gas flows through the fluid control device described, the dead volume is limited only to the short channels 25, 26 connecting each main channel 21 to the corresponding second and third valve actuators 5, 6.

[0030] FIG. 5 shows a second embodiment of shutoff-opening device 31 of the invention. The shutoff-opening device 31 is provided at each of the inlet side and outlet side of a massflow controller 2 to constitute a fluid control device 40 as seen in FIG. 6. This shutoff-opening device 31 is different from the shutoff-opening device 1 of the first embodiment in that a first subchannel 32 has

an opening in the lower surface of a valve main body 33. Throughout the drawings showing the first and second embodiments, like parts are designated by like reference numerals and symbols and will not be described repeatedly hereinafter. With reference to FIG. 5, the fitting 9 at the front end of the valve main body 3 shown in FIG. 1 is removed, and the main body 33 has a block-like extension 34, which is formed with the first subchannel 32 which has an opening in the lower surface of the valve main body, in addition to the second and third subchannels 23, 24. As seen in FIG. 6, the extension 34 has connected thereto a piping channel block 35 communicating with the first subchannel 32, in addition to the piping channel blocks 15, 16 in communication with the respective second and third subchannels 23, 24. A fitting 36 provided under this piping channel block 35 has a pipe joint, which is positioned at a level intermediate between the evacuation pipe 27 and the fitting 28 communicating with the second subchannel 23. Accordingly, the process gas piping is unlikely to interfere with the purge gas piping or the evacuation pipe 27.

[0031] Although the shutoff-opening devices 1 shown in FIGS. 1, 2 and 5 have three valve actuators 4, 5, 6, two actuators are used when there is no need for the evacuation subchannel 24. In this case, the third valve actuator 6 is of course eliminated with the front-to-rear length of the valve main body shortened, whereas FIG. 7 shows a valve main body 43 which has the same length as the foregoing embodiments but which is formed with neither of the cavity 19 for inserting the third actuator 6 and the evacuation subchannel 24.

[0032] FIG. 7 shows a shutoff-opening device 41, which comprises a generally rectangular parallelepipedal valve main body 43, and first (front-end) and second valve actuators 4, 5 mounted on the upper surface of the main body 43 and arranged side by side longitudinally thereof (front-rear direction). The main body 43 is internally formed with a main channel 21 extending from the rear end face of the body 43 to a location near the front end thereof, and first (front-end) and second subchannels 22, 23 adapted to communicate with the main channel 21 under the control of the respective actuators 4, 5. The upper surface of the valve main body 43 includes a mount face 43a in the form of a slanting face extending forwardly downward and having the frontside first actuator 4 mounted thereon. The other portion of the surface, i.e., mount face 43b, is flat and parallel to the lower surface of the body 43. The flat face 43b has such an area that two valve actuators can be mounted thereon. The front half of the flat face 43b has the second actuator 5 mounted thereon.

[0033] A pressure sensor can be mounted on the portion of the shutoff-opening device shown in FIG. 7 at the portion from which the third actuator 6 is removed as shown in FIG. 8. With reference to FIG. 8, a shutoff-opening device 51 thus adapted comprises a generally rectangular parallelepipedal valve main body 53, and first (front-end) and second valve actuators 4, 5 mount-

ed on the upper surface of the main body 53 and arranged side by side longitudinally thereof (front-rear direction). The main body 53 is internally formed with a main channel 21 extending from the rear end face of the body 53 to a location near the front end thereof, and first (front-end) and second subchannels 22, 23 adapted to communicate with the main channel 21 under the control of the respective actuators 4, 5. The upper surface of the valve main body 53 includes a mount face 53a in the form of a slanting face extending forwardly downward and having the front-end first actuator 4 mounted thereon. The other portion of the surface, i.e., mount face 53b, is flat and parallel to the lower surface of the body 53. The flat face 53b has such an area that two valve actuators can be mounted thereon. The front half of the flat face 53b has the second actuator 5 mounted thereon. The rear half portion is formed with a threaded bore 54 for mounting a pressure sensor. The valve main body 53 is provided at its front end with a fitting 55 which is externally threaded.

[0034] The fluid control devices 10, 40 shown in FIGS. 3, 4 and 6 are used in a suitable combination to provide a fluid control apparatus for use in fabricating semiconductors. FIG. 9 shows an example of such fluid control apparatus. With reference to the drawing, the fluid control device 40 including shutoff-opening devices 31 each having two valve actuators 4, 5 is disposed in parallel to the fluid control device 10 including shutoff-opening devices 1 each having three valve actuators 4, 5, 6 without no spacing formed between the two devices 40. 10. Although not shown, another similar fluid control device can be disposed in parallel to these devices 10, 40 without being spaced apart therefrom.

[0035] Thus fluid control apparatus can be provided wherein these fluid control devices 10, 40 are in a planar or flat arrangement, with the first actuators 4 of the shutoff-opening devices 1, 31, as well as the second actuators 5 thereof, arranged in alignment with one another. Further the piping means 15, 16, 27, 28 for the second and third subchannels 23, 24 are provided under a base plate 29 (rear side of the drawing) without increasing the width of the overall control apparatus. These piping portions 15, 16, 27, 28 are easy to maintain and appear neat.

[0036] According to the arrangement shown in FIG. 9, the same shutoff-opening devices 1 or 31 are disposed at the inlet side and the outlet side of each mass-flow controller 2, and the extensions 7, 8 of the valve main bodies 3, 33 are provided at left on the inlet side and at right on the outlet side. On the other hand, FIG. 10 shows a fluid control apparatus wherein extensions 46, 47 of valve bodies 44, 45 at the inlet side and the extensions 7, 8 of the valve bodies 1, 31 at the outlet side are similarly arranged at right. These inlet-side valve main bodies 44, 45 are available, for example, merely by changing the position of the extension 7 on the right side as shown in FIG. 1 to the left side and causing the main channel 21 to communicate with the

channels in the interior of the extension 7. With this arrangement, the second and third subchannels 23, 24 are all made to communicate with openings in the underside, while the openings are all positioned at the right side of the valve main bodies, consequently assuring facilitated piping work.

[0037] When the shutoff-opening devices 1, 31, 41, 51 according to the first to fourth embodiments are to be used, lower channel blocks 12 are necessary for connecting the massflow controller 2 to the shutoff-opening devices 1, 31, 51 as shown in FIG. 3 or 6. The lower channel block 12 is fastened to the valve main body 3 with the device installing screws 14 driven in through the Lower block 12 horizontally. In removing the shutoff-opening device 1, 31, 41 or 51, these screws 14 and piping installing screws 17 need to be removed, whereas the removal of the device installing screws 14 requires a very cumbersome procedure in the case where many control devices 10, 40, or 20, 50 have been assembled as arranged in parallel into a fluid control apparatus (see FIG. 9 or 10).

[0038] Two embodiments will be described below which ensure facilitated removal of the shutoff-opening devices.

[0039] FIGS. 11 and 12 show a fifth embodiment of shutoff-opening device of the invention. This shutoff-opening device 101 has the same construction as the shutoff-opening device 31 of the second embodiment shown in FIG. 5 except that a main channel 121 has no opening in a rear end face 103c but communicates with an opening formed in the lower surface of a valve main body 103 by way of a downward channel 122 provided in the body 103.

[0040] Throughout the drawings showing the first, second and the following embodiments, like parts are designated by like reference numerals or symbols and will not be described repeatedly.

[0041] With reference to FIGS. 11 and 12, the valve main body 103 is internally formed with the above-mentioned main channel 121 which extends from a portion close to the rear end of the body 103 nearly to the front end thereof, and first (front-end), second (intermediate) and third (rear-end) subchannels 32, 23, 24 communicating with the main channel 121 via respective valve actuators 4, 5, 6. The main channel 121 has the downward channel 122, which extends straight from the rear end of the channel 121 downward and has an opening in the lower surface rear end portion of the body 103. The subchannels 32, 23, 24 extend through a blocklike extension 34 of the valve main body 103 and are open at the lower surface of the body 103. The upper surface of the valve main body 103 includes a mount face 103a which is in the form of a slanting face extending forwardly downward and having the front-end first valve actuator 4. The other portion of the surface is a mount face 103b for the other two second and third valve actuators 5, 6.

[0042] With reference to FIG. 12, the dead volume of

the shutoff-opening device 101 is only the short channels 25, 26 connecting the main channel 121 to the respective second and third valve actuators 5, 6 when a fluid flows from the main channel 121 into the first subchannel 32. When the fluid flows from the main channel 121 into the second subchannel 23, the dead volume is the short channel 26 connecting the main channel 121 to the third actuator 6, and front end portions 121a, 121b of the main channel 121 which are positioned between the first and second actuators 4, 5, forming an obtuse angle. When the fluid flows from the main channel 121 into the third subchannel 24, the dead volume is the short channel 25 connecting the main channel 121 to the second actuator 5, the main channel front end portions 121a, 121b positioned between the first and second actuators 4, 5, and an intermediate portion 121c of the main channel 121 positioned between the second and third actuators 5, 6.

[0043] FIGS. 13 and 14 show a fluid control device 140 comprises two shutoff-opening devices 101. The device 140 shown in FIG. 13 is characterized in that unlike the fluid control device 10 shown in FIG. 3, the device 140 has no lower channel blocks 12 and therefore none of the device installing screws 14 horizontally driven through the blocks 12. Each channel block 11 joined to a massflow controller 2 has a channel 11a, which has a lower opening and is held in communication with the downward channel 122 by a pipe fitting 123 below the valve main body 103.

[0044] In this way, the space under the valve main body 103 is used for piping not only for the first, second and third subchannels 32, 23, 24 but also for the main channel 121, whereby the devices, such as the massflow controller 2 and shutoff-opening devices 101, which are mounted on the upper side of a base plate 29 are completely separated from the piping means, such as channel blocks 15, 16, 35, fittings 28, 36 and pipe 27, which are arranged under the plate 29. If the massflow controller 2 of the fluid control device 140 malfunctions, the controller 2 is removable upward for replacement by removing the controller installing screws 13. Further if the shutoff-opening device 101 fails, the device 101 can be removed upward for replacement by removing the piping installing screws 17 and the piping installing screws 17. The piping portion can then be in a flat arrangement under the valve main body, compacting the control apparatus in its entirety and assuring the component devices and the piping means of greatly facilitated maintenance.

[0045] FIGS. 15 and 16 show a sixth embodiment of shutoff-opening device of the invention. This shutoff-opening device 131 is similar to the shutoff-opening device 101 of fifth embodiment shown in FIGS. 11 and 12 in that the main channel 121 has no opening in a rear end face 133c but communicates with an opening formed in the lower surface of a valve main body 133 via a downward channel 132 formed in the body 133. The shutoff-opening device 131 differs from the device

101 in that the downward channel 132 extends from an intermediate portion of the main channel 121 (between the second and third actuators 5, 6) to the opening in the lower surface of the valve main body 133 through a blocklike extension 34 of the body 133. The shutoff-opening device 131 provides a fluid control device, which has the same feature as the fluid control device 140 shown in FIGS. 13 and 14.

[0046] Incidentally, shutoff-opening devices 1, 31, 41, 51, 101, 131 may of course be attached to devices other than the massflow controller 2, and are of course usable for passing liquids instead of gases.

Claims

1. A shutoff-opening device comprising a generally rectangular parallelepipedal valve main body (3, 33, 43, 53, 103, 133) having substantially parallel upper and lower surfaces joined at their opposite ends by front and rear end surfaces; said valve main body (3, 33, 43, 53, 103, 133) being internally formed with a main channel (21, 121) having an inlet opening disposed on said rear end surface of said valve main body (3, 33, 43, 53, 103, 133) or rear end portion of the lower surface of said valve main body (3, 33, 43, 53, 103, 133) and extending essentially along a straight line from said rear end toward said front end of the main body (3, 33, 43, 53, 103, 133); a plurality of a channel on-off actuators (5, 6) mounted on the upper surface of the valve main body (3, 33, 43, 53, 103, 133) in a side-by-side relation longitudinally of said upper surface with the central axis of said actuators (5, 6) being perpendicular to said upper face, the actuators (4, 5, 6) being actuable to selectively open and close communication between a subchannel (22, 23, 24) and an associated short channel (25, 26) extending from the seat of each actuator (5, 6) in axial alignment with the central axis thereof into communication with said main channel (21, 121) and co-operating with said main channel (21, 121) to form a dead volume when said actuators (4, 5, 6) are in a closed condition, **characterized in that** the upper surface of said valve main body (3, 33, 43, 53, 103, 133) at the front end thereof includes a slanting face (3a, 43a, 53a, 103a, 133a) extending forwardly downward and has the front-end valve actuator (4) mounted thereon, wherein the associated short channel extends from the front-end valve actuator (4) in axial alignment therewith to the main channel (21, 121).
2. A fluid control device **characterized in that** it comprises a shutoff-opening device (1, 31) according to claim 1, which is disposed at each of an inlet side and an outlet side of a controller (2) for regulating

the pressure or flow rate of fluids.

3. A fluid control apparatus **characterized in that** it comprises fluid control devices as defined in claim 2, which are arranged side-by-side, the valve main bodies (3, 33) of the shutoff-opening devices (1, 31) being equal in front-to-rear length irrespective of the number of valve actuators (4, 5, 6) mounted on the respective upper surfaces thereof.
4. A fluid control apparatus as defined in claim 3, **characterized in that** the subchannel (22) of each shutoff-opening device communicating with the respective main channel (21, 121) via the front-valve actuator (4) as an opening formed in the front-end face of the valve main body (3) and the other subchannel or subchannels (23, 24) have an opening in the lower surface of the valve main body (3), pipings (15, 16, 27, 28) for said other subchannel or subchannels (23, 24) being provided below the main body (3).
5. A fluid control apparatus as defined in claim 4, **characterized in that** all subchannels (22, 23, 24) of each shutoff-opening device has an opening formed in the lower surface of the valve main body (3), piping for each sub channel being provided below the main body (3).

Patentansprüche

1. Eine Absperr-Öffnungs-Vorrichtung mit einem Ventilhauptkörper (3, 33, 43, 53, 103, 133), der eine rechteckige parallelepipedale Grundform mit im wesentlichen parallelen Ober- und Unterseiten, welche an ihren gegenüberliegenden Enden durch vordere und hintere Endflächen verbunden sind, aufweist; wobei der Ventilhauptkörper (3, 33, 43, 53, 103, 133) intern mit einem Hauptkanal (21, 121) versehen ist, der eine Einlaßöffnung besitzt, welche an der hinteren Endfläche des Ventilhauptkörpers (3, 33, 43, 53, 103, 133) oder an dem hinteren Endbereich der Unterseite des Ventilhauptkörpers (3, 33, 43, 53, 103, 133) angeordnet ist und der sich entlang einer geraden Linie von dem hinteren Ende in Richtung des vorderen Endes des Hauptkörpers (3, 33, 43, 53, 103, 133) erstreckt; und mit einer Vielzahl von Ein-Aus-Stellgliedern (5, 6), die an der Oberseite des Ventilhauptkörpers (3, 33, 43, 53, 103, 133) Seite an Seite in der Längsrichtung der Oberseite angeordnet sind, wobei die zentrale Achse der Stellglieder (5, 6) senkrecht zu der Oberseite steht und die Stellglieder (4, 5, 6) betätigbar sind, um wahlweise eine Verbindung zwischen einem Nebkanal (22, 23, 24) und einem zugeordneten kurzen Kanal (25, 26), der sich von

dem Sitz eines jeden Stellglieds (5, 6) in axialer Ausrichtung zu der zentralen Achse von diesem in Verbindung mit dem Hauptkanal (21, 121) erstreckt, und mit dem Hauptkanal (21, 121) zusammenarbeitet, um ein Totvolumen zu bilden, wenn die Stellglieder (4, 5, 6) sich in einem geschlossen Zustand befinden, herzustellen oder zu unterbrechen,

dadurch gekennzeichnet, daß

die Oberseite des Ventilhauptkörpers (3, 33, 43, 53, 103, 133) an ihrem vorderem Ende eine geneigte Fläche (3A, 43A, 53A, 103A, 133A) aufweist, in welche sich nach vorne unten erstreckt und an dem ersten Ventilstellglied (4) für das vordere Ende montiert ist, wobei sich der zugeordnete kurze Kanal von dem Ventilstellglied (4) für das vordere Ende in axialer Ausrichtung zu diesem zu dem Hauptkanal (21, 121) erstreckt.

2. Eine Fluidsteuerungsvorrichtung, **dadurch gekennzeichnet**, daß sie eine Absperr-Öffnungs-Vorrichtung (1, 31) nach Anspruch 1 aufweist, die jeweils an einer Einlaßseite und einer Auslaßseite eines Reglers (2) zur Regulierung des Drucks oder der Durchflussgeschwindigkeit eines Fluids angeordnet ist.
3. Ein Fluidsteuerungsgerät, **dadurch gekennzeichnet**, daß es Fluidsteuerungsvorrichtungen wie in Anspruch 2 definiert aufweist, die Seite an Seite angeordnet sind, wobei die Ventilhauptkörper (3, 33) der Absperr-Öffnungs-Vorrichtungen (1, 31) unabhängig von der Anzahl von Ventilstellgliedern (4, 5, 6), die an den entsprechenden Oberseiten davon angeordnet sind, eine gleiche Länge von vorne nach hinten besitzen.
4. Ein Fluidsteuerungsgerät wie in Anspruch 3 definiert, **dadurch gekennzeichnet**, daß der Nebkanal (22) von jeder Absperr-Öffnungs-Vorrichtung, der mit dem entsprechenden Hauptkanal (21, 121) über das frontseitige Ventilstellglied (4) in Verbindung steht, eine Öffnung besitzt, die in der frontseitigen Endfläche des Ventilhauptkörpers (3) ausgebildet ist, und der andere Nebkanal bzw. die anderen Nebkanäle (23, 24) eine Öffnung in der Unterseite des Ventilhauptkörpers (3) aufweisen, wobei Rohrleitungen (15, 16, 27, 28) für den anderen Nebkanal bzw. die anderen Nebkanäle (23, 24) unterhalb des Hauptkörpers (3) vorgesehen sind.
5. Ein Fluidsteuerungsgerät wie in Anspruch 4 definiert, **dadurch gekennzeichnet**, daß alle Nebkanäle (22, 23, 24) von jeder Absperr-Öffnungs-Vorrichtung eine Öffnung haben, die an der Unterseite des Ventilhauptkörpers (3) ausgebildet ist, wobei Rohrleitungen für jeden Nebkanal unterhalb des Hauptkörpers (3) vorgesehen sind.

Revendications

1. Un dispositif de fermeture / ouverture comprenant un corps principal de valve (3, 33, 43, 53, 103, 133) de la forme d'un rectangle généralement parallélépipède ayant des surfaces supérieures et inférieures essentiellement parallèles jointes à leurs extrémités opposées par des surfaces avant et arrière ; ledit corps principal de valve (3, 33, 43, 53, 103, 133) étant formés à l'intérieur d'un canal principal (21, 121) ayant une ouverture d'entrée disposée sur ladite surface arrière et dudit corps principal de valve (3, 33, 43, 53, 103, 133) ou sur une partie terminale arrière de la surface inférieure dudit corps principal de valve (3, 33, 43, 53, 103, 133) et s'étendant essentiellement le long d'une ligne droite à partir de ladite extrémité arrière vers ladite extrémité avant du corps principal de valve (3, 33, 43, 53, 103, 133) ; une multitude d'actuateurs (5, 6) on / off de canal montés sur la surface supérieure du corps principal de valve (3, 33, 43, 53, 103, 133) dans une relation côte à côte de manière longitudinale de ladite surface supérieure avec l'axe central desdits actuateurs (5, 6) étant perpendiculaires par rapport à ladite surface supérieure, les actuateurs (4, 5, 6) étant actionnés pour ouvrir et fermer de manière sélective la communication entre un sous-canal (22, 23, 24) et un canal court associé (25, 26) s'étendant à partir de l'endroit de chaque actuateur (5, 6) dans un alignement axial avec l'axe central pour communiquer avec ledit canal principal (21, 121) et coopérant avec ledit canal principal (21, 121) pour former un volume mort lorsque lesdits actuateurs (4, 5, 6) sont fermés, **caractérisé en ce que**, la surface supérieure dudit corps principal de valve (3, 33, 43, 53, 103, 133) sur l'extrémité avant / frontale comprend une face inclinée (3a, 43a, 53a, 103a, 133a) s'étendant vers l'avant en descendant et l'actuateur (4) de valve avant-arrière étant monté sur ladite face ; où le canal court associé s'étend à partir de l'actuateur (4) de valve avant-arrière dans un alignement axial par rapport au canal principal (21, 121).
2. Un dispositif de contrôle de fluide **caractérisé en ce qu'il** comprend un dispositif de fermeture / ouverture (1, 31) selon la revendication 1 qui est disposé sur chacune des formes d'entrée et de sortie d'un contrôleur (2) pour réguler la pression du débit fluides.
3. Un appareil de contrôle de fluide **caractérisé en ce qu'il** comprend des dispositifs de contrôle de fluide comme défini dans la revendication 2 qui sont disposés côte à côte, les corps principaux de valve (3, 33) des dispositifs de fermeture / ouverture (1, 31) étant égaux dans leur longueur avant vers arrière peu importe le nombre d'actuateurs de valve (4, 5,

6) montés sur les surfaces supérieures respectives.

4. Un appareil de contrôle de fluide comme défini dans la revendication 3, **caractérisé en ce que** le sous-canal (22) de chaque dispositif de fermeture / ouverture communiquant avec le canal principal respectif (21, 121) par l'intermédiaire de l'actuateur (4) de valve avant a une ouverture formée dans la face avant-arrière du corps principal de valve (3) et **en ce que** l'autre canal ou sous-canaux (21, 24) ont une ouverture dans la surface inférieure du corps principal de valve (3); des tuyaux (15, 16, 27, 28) destinés pour ledit autre sous-canal ou sous-canaux (23, 24) étant pourvus sous le corps principal (3).

5. Un appareil de contrôle de fluide comme défini dans la revendication 4, **caractérisé en ce que** tous les sous-canaux (22, 23, 24) de chaque dispositif de fermeture / ouverture ont une ouverture formée dans la surface inférieure du corps principal de valve (3), la tuyauterie destinée pour chacun des sous-canaux étant fournie sous le corps principal (3).

FIG. 1




FIG. 2




FIG. 3




FIG. 5





FIG. 4







FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG.12




FIG.13




FIG. 14




FIG.15




FIG.16





FIG. 17



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.